

apex
CLINICAL SCALES

**APEX-RI
SERIES**
PORTABLE SCALES
WITH
**REMOTE
INDICATOR**



- 600 lb x 0.2 lb /
300 kg x 0.1 kg
- Wi-Fi and Bluetooth® available
- Portable with built-in carrying handle
- Remote indicator for versatile display placement
- Spacious 17 x 17 in / 43 x 43 cm platform

APEX-RI SERIES REMOTE INDICATOR PORTABLE SCALES

DETECTO
www.Detecto.com

These digital flat scales let the patient weighing come to you!



DETECTO
Model APEX-RI

WHERE SPACE IS LIMITED
THERE IS STILL ROOM FOR DETECTO'S APEX-RI SERIES SCALES AND THEIR VERSATILE MEASUREMENT FEATURES

- Body Mass Index Calculation
- Textured Platform Surface for Safety
- 6 Easy-to-Use Buttons
- Auto Weight Lock Feature
- Power-up Zero
- StableSENSE® Adjustable Filtering
- High 600-lb / 300-kg Capacity for Bariatric Patients
- Bluetooth (BLE) / Wi-Fi Available (models -BT)
- 12VDC AC Power Adapter Included on -AC models

DETECTO's apex® series APEX-RI model portable scales feature an extra-wide, flat platform measuring 17 in W x 17 in D x 2.75 in H. The apex® scales offer a high 600 lb x 0.2 lb / 300 kg x 0.1 kg capacity, 0.75-inch-high clinical-blue LCD weight readouts, BMI calculation for checking nutritional status, AC or 12 AA battery power (AC adapter included on some models), (2) RS232 serial ports, (1) micro USB-B port, and HL7 IEEE 11073 compliance. They are ready to use right out of the box in just a few seconds with no assembly needed.




Thanks to the apex® scale's carrying handle, compact size, and minimal weight it can easily be transported wherever needed.



Lift-Off Platform Cover

The lift-off apex® platform cover may be removed for easy wipe-down cleaning or to quickly replace the 12 AA batteries. The scale's structural base integrity is manufactured rock-solid for optimal patient safety and stability.

SMART-PHONE STYLE HIGH-TECH WEIGHT INDICATOR



The 6 ft/1.8 m cable from the scale base to indicator allows you to place the display wherever it's easiest to read

The apex® features a high-tech, smart-phone-style indicator for easy utilization with 6 simple buttons and a bold LCD display for large readouts.


- 0.75-inch-high, clinical-blue LCD weight readouts
- Body Mass Index calculation
- Weight and height displayed onscreen simultaneously
- Automatically locks on weight temporarily for a few seconds in order to easily view and record measurement
- Battery power level indication

*Ready To Use
Right Out of
the Box (No
Assembly
Required)*



Wall-Mount or Desktop Mounting Bracket Included

The display can be set up separately from the base and read from its position on the wall or desk making it suitable for stationary or mobile use.



VERSATILE CONNECTIVITY:

- (1) micro USB-B port
- (2) RS232 serial ports
- HL7 IEEE 11073 compliant (standard)
- Wi-Fi models available*
- Bluetooth models available*

** Protocol available upon request.*



APEX-RI SERIES

PORTABLE SCALES
WITH
**REMOTE
INDICATOR**

Model	APEX-RI	APEX-RI-AC	APEX-RI-BT	APEX-RI-BT-AC
Capacity	600 lb x 0.2 lb / 300 kg x 0.1 kg (lb or kg selected upon initialization at start-up)			
Platform Size	17 in W x 17 in D x 2.75 in H / 43 cm W x 43 cm D x 7 cm H			
AC Adapter		•		•
Bluetooth/Wi-Fi			•	•
Weighing/ Height Units	Pounds/Inch (lb, in) or Kilograms/Centimeters (kg, cm)			
Power	12 AA cell Alkaline, Ni-Cad or NiMH batteries (not included) or optional 100-240 VAC 50/60Hz 12 VDC 1A wall plug-in UL/CSA listed AC power adapter (DETECTO part number 6800-1047 with multi-pin-input, snap-in choices for US, UK, EU, Australia, and Japan)			
Ports	(2) RS232 serial ports and (1) micro USB-B port			
Device Connectivity	HL7 IEEE 11073 compliant (standard) Wi-Fi/Bluetooth BLE models also available Protocol available upon request			
Keypad	Mechanical switch type with 6 buttons (Power, Lock/Release, Zero, BMI/Enter, Up Arrow, Down Arrow)			
Cable Length	6 ft / 1.8 m (from scale base to indicator)			
Display Type	Dual-row, seven-segment, clinical-blue LCD			
Number of Characters	Weight: 5 digit, 0.75 in (19 mm) high / Height/BMI: 4 digit, 0.4 in (10 mm) high			
Operating Environment	Operating Temperature Range: 14 to 104 °F (-10 to +40 °C) / Humidity: 0 to 90% non-condensing			
Digital Filtering	StableSENSE® adjustable filtering			
Country of Origin	USA			
Net Weight	25 lb / 11 kg			
Shipping Weight	31 lb / 14 kg			
UPC Code	809161304107	809161304206	809161304305	809161304404



International Power Available

AC adapter included on all -AC models with multi-pin-input, snap-in choices for US, UK, EU, Australia, and Japan. DETECTO part number 6800-1047: 100-240VAC/12VDC at 1 amp.



DETECTO reserves the right to improve, enhance, or modify features and specifications without prior notice.



203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 1-800-641-2008 Fax: 417-673-2153

Mobile: m.detecto.com

SOLD BY: