PS500

Compact, Light Weight Floor Scale

Shown with optional floor stand

- **Accuracy–** 0.2% of full capacity

- **Capacity–** 500 lb (250 kg)

- **Construction–** Low profile stainless steel platform with mild steel understructure and stainless steel/ABS indicator.

- **Platform Size–** 22" x 22", 22" x 36", and 22" x 42"

- **Protocol–** Standard NCI interfaces to most common shipping software, including UPS™ Worldship Online and FedEx®. Not legal for trade

- **Display–** Five 0.625" digits LCD

- **Power–** Battery or AC power

- **Operator Keys–** On/Off/Zero, Tare, Units (lb/kg), Hold/Print

- **Options–** Floor and table top stands for the weight indicator

VALOR EN PESAJE

PS500 Compact, Light Weight Floor Scale

Features

Salter Brecknell PS500 offers a convenient, compact and portable weighing capability with high capacity.

This durable product offers unparalleled weighing performance, with the advantages of low profile and affordability.

Standard features include lbs, kg and lb/oz weighing modes, weight hold feature, stable weight indication and auto power off to extend battery life.

Operates on four (4) AAA batteries or AC adapter (both included). Also included is a rubber slip reducing mat, an indicator bracket for stand or wall mounting, and a RS-232 cable.

PS500 comes with a stainless steel top, allowing for easy wipedown.

Not legal for trade.

Shown with optional floor stand

Shown with optional table top stand

Specifications

Capacity– 500 lb x 0.2 lb (250 kg x 0.1 kg)

Platform Size–
Scale: 22" L x 22" W x 2" H
559 mm (L) x 559 mm (W) x 51 mm (H)

36" L x 22" W x 2" H
906 mm (L) x 559 mm (W) x 51 mm (H)

42" L x 22" W x 2" H
1067 mm (L) x 559 mm (W) x 51 mm (H)

Indicator– 6.5" L x 3.2" H x 1.2" W
164 mm (L) x 81 mm (H) x 29 mm (W)

Display– Five 0.625" digits LCD

RS-232– 10' interface cable (DB-9) (included)

Keyboard– Hold/Print, Units, Tare, On/Off/Zero

Units– lb, kg, lb/oz

Power– Four (4) AAA batteries or 6 VDC, 500mA adapter (both included)

Battery Life– 20 hours

Operating Temp– 41° F to 95° F (5° C to 35° C)

Packaging Dimensions–
Scale: 26" L x 24" W x 4" H
660 mm (L) x 609 mm (W) x 101 mm (H)

39" L x 24" W x 4" H
965 mm (L) x 609 mm (W) x 101 mm (H)

44" L x 24" W x 4" H
1117 mm (L) x 609 mm (W) x 101 mm (H)

Shipping Weight–
35 pounds (16 kg) - 22" (607 mm)
57 pounds (26 kg) - 36" (914 mm)
63 pounds (29 kg) - 42" (1067 mm)

Options–
Table top stand (not included)
Stand height: 19.125" (486 mm); weight 3 lb (1.5 kg)
Stand base: 6" W x 3" L x 1" H
152 mm (W) x 76 mm (L) x25 mm (H)

Floor stand (not included)
Stand height: 36" (914 mm); weight 11 lb (5 kg)
Stand base: 11.5" L x 11.5" W x 0.75" H
292 mm (L) x 292 mm (W) x 19 mm (H)

Certifications– Full FCC compliance, UL/CUL power adapter